Aluminium Ball Wheel Castor

- Ø50x48mm ball wheel, with black PU tread
- Loading capacity: 40 kg/pc

ABL50DBB



ZPT-ABL50DBB-61AB (non-brake)

ABL50DBB-62ABB-T15 (with brake)

ABL50ABN



ABL50ABN-61BN-T15 (non-brake)

ZPT-ABL50ABN-62BNT (with brake)

• With M10x15mm (T15) threaded bolt stem



ABL50-61-T15 (non-brake)



ABL50-62-T15 (with brake)

Model	Finish (wheel / yoke)	Brake
ABL50DBB-61AB-T15	rustic brass / antique brass	non-brake
ABL50DBB-62ABB-T15	rustic brass / antique brass	with brake
ABL50ABN-61BN-T15	brushed inox / brushed nickel	non-brake
ABL50ABN-62BNT-T15	brushed inox / brushed nickel	with brake



ZPT-ABL50-61-PT1 (non-brake)



ZPT-ABL50-62-PT1 (with brake)

Model	Finish (wheel / yoke)	Brake
ZPT-ABL50DBB-61AB	rustic brass / antique brass	non-brake
ZPT-ABL50DBB-62ABB	rustic brass / antique brass	with brake
ZPT-ABL50ABN-61BN	brushed inox / brushed nickel	non-brake
ZPT-ABL50ABN-62BNT	brushed inox / brushed nickel	with brake